



PRODUCT NAME:
GLOBAL STAINLESS SERIES
S/S EXPOSED ADJUSTABLE BREACH
WALL TAP WITH STANDARD SPOUT

PART NUMBER:
GS15S3006 + others

DESCRIPTION:
S/S EXPOSED ADJUSTABLE WALL TAP BODY
with 360 DEGREE SWIVEL CHECK STEMS
JUMPER VALVES.

TECHNICAL INFORMATION:
- IDEAL WORKING PRESSURE:- 65 - 100 PSI
- REC. MIN. OPERATING PRESSURE :- 45 PSI
- MAXIMUM PRESSURE = 200 PSI STATIC (in short periods)
- WORKING TEMPERATURE 5 C - 65 C

SUPPLIED WITH:
- S/S 360 DEGREE SWIVEL CHECK STEMS JUMPER VALVES
- S/S SPOUT
- S/S ADJUSTABLE WALL MOUNTS
- CP ADJUSTABLE SCREWED WALL FLANGE

FEATURES:
TAP BODY:
- S/S BODY
- S/S INTERNAL WORKINGS
- CP LEVER HANDLES (SMALL FLAT EDGE SHAPE)
- ADJUSTABLE UP TO 13MM

WELS
- 3 STAR, 9lpm

TAP WITH S/S SPOUT.	REF	LENGTH IN/MM
GS15S3006	A	6" /179mm
GS15S3008	B	8" /227mm
GS15S3010	C	10" /276mm
GS15S3012	D	12" /326mm
GS15S3014	E	14" /376mm

WATERMARK & WELS:

Global Tapware Pty Ltd is a Watermarked, level 1, Company.
All relevant products & components are WELS registered.

Special Notice:

- 1 - We reserve the right to make changes to products and drawings without notice.
- 2 - All drawings & Documents are subject to copyright ©.
- 3 - Seek written consent by us to reprint / use for other than specification work

GLOBAL STAINLESS SERIES PT NO.GS15S3006 (+)
S/S EXPOSED BREACH adj.WALL TAP w/- S/S STDD SPOUT

