



**PRODUCT NAME:**  
**'GLOBAL RINSE MAID®' Series**  
PRE RINSE SUB ASSEMBLY - STANDARD

**'Australian Designed  
& Made'**

**PART NUMBER:**  
GRM2100

**DESCRIPTION:**  
"GLOBAL RINSE MAID" STANDARD PRE RINSE  
SUB ASSEMBLY (16" RISER)

**TECHNICAL INFORMATION:**  
- IDEAL WORKING PRESSURE 65 - 100 PSI  
- MAXIMUM PRESSURE = 200 PSI STATIC  
(in short periods)  
- WORKING TEMPERATURE 5 C - 65 C  
- SHIPPING WEIGHT \_\_\_\_\_ KGS (approx)  
- THREADED MECHANICAL JOINTS

**SUPPLIED WITH:**  
- CP SPRAY GUN (3.5LPM) WELS 6 STAR  
- S/S BRAIDED HOSE WITH PLASTIC COATING  
- CP SPRING GUARD & HOOK  
- CP 16" RISER  
- CP WALL BRACKET

**FEATURES:**

**S/S BRAIDED / PLASTIC COATED HOSE:**  
- 12mm i.d. S/S BRAIDED w/- PLASTIC COATING  
- 850mm approx. (33 INCHES approx.)  
- C.P. 1/2" Female SWIVEL END FITTINGS

**WALL BRACKET:**  
- ADJUSTS FROM 50mm TO 300mm  
- 3 SCREW HOLE BACK PLATE FOR EASY FIXING TO STUDS

**SPRAY VALVE & HANDLE:**  
- CHROME PLATED BRASS  
- INSULATED BLACK HANDLE  
- FLAT CHROME PLATED METAL SQUEEZE LEVER WITH  
INSULATION COVERING & FLAT WIDE STOPPER.  
- SQUEEZE LEVER IS CONSTANT IN MAINTAINING IT'S POSITION.  
- QUICK RELEASE ON/OFF CLIP ON SQUEEZE LEVER = good OH&S  
- 15 DEGREE FLAT HIGH PRESSURE SPRAY FOR BEST CLEANING

**ADDITIONAL SPRAY VALVE INFO**  
- LOW ENERGY CONSUMPTION = **HIGH \$ SAVINGS**  
- LOW WATER CONSUMPTION = **HIGH \$ SAVINGS**  
- ENGINEERED TO OUT PERFORM OTHER BRANDS  
- EXTREMELY ROBUST & ENGINEERED TO LAST

**WELS**  
-6 STAR, 3.5 lpm

**WATERMARK & WELS:**

Global Tapware Pty Ltd is a Watermarked, level 1, Company.  
All relevant products & components are WELS registered.

**Special Notice:**

- 1 - We reserve the right to make changes to products and drawings without notice.
- 2 - All drawings & documents are subject to copyright (c).
- 3 - Seek written consent by us to reprint / use other than in specification work.

**'GLOBAL RINSE MAID®' Series PT No. GRM2100**  
**PRE RINSE SUB ASSEMBLY -STANDARD**

