

UNIVERSAL PR HOSE
The Complete Pre Rinse Hose Replacement Kit
Pt. No.- GF2918A



This kit is designed to fit to most commercial brands of Pre Rinse units on the Australian market. It has been brought about by constant complaints from merchants & plumbers alike that it is too hard & time consuming to find the right hose with the right fittings. Now those complaints have been answered with the '**Global Fisher**' hose kit **F2918A**

FITS TO:-

- ✓ The New watermarked 'Global Fisher' & the older model 'Fisher' Pre Rinses.
- ✓ The New watermarked 'Global Rinse-Maid' & 'Global Q' Pre Rinses.
- ✓ Enware brand of Pre Rinses.
- ✓ Galvin brand of Pre Rinses.
- ✓ LW Gemmel brand of Pre Rinses.
- ✓ T&S brand of Pre Rinses. (No longer available in Australia)
- ✓ Encore brand of Pre Rinses. (No longer available in Australia)
- ✓ Other Pre Rinses that have a 1/2" bsp female hose ends.

Features:-

1. 36" S/S Armourflex outer sleeve = High performance and greater flexibility.
2. Longer lasting than most on the market.
3. 3 ply inner core that will out perform and out last other similar brands.
4. Handle suits Fisher / Enware / LGW / T&S / Encore spray valves only.
5. A range of adaptors to screw onto ends of hose to suit just about every configuration in the market.
6. Fittings & Hose narrow enough to slide through all or most Spring Guards.





Note- You may not use some fittings but we suggest you keep these for some future use as we do offer two other models of hoses- F2918 & F2914. However, this is the best unit to keep in stock or on board your van / ute to cover all contingencies.

Warranty :-






We offer a 6-month warranty on this unit for faulty materials and / or workmanship only. We do not take any responsibility for Installation or for an incorrect install, i.e. fitted with short end of spring on the Spring Retainer.

Fitting Universal Pre Rinse Hose Replacement Kit. Pt. No.- GF2918A





❖ **Fitting to 'Global Fisher' / older model 'Fisher' / 'Global Rinse-Maid' / 'Global Q'**

-  Using PST sealant or a quality thread seal tape (pink or blue) carefully screw 1/4" male thread on hose into the 'Spring Retainer'. Take care to NOT undo this 1/4 fitting from inner hose.
-  Slide Hook then Spring over hose and rest on above adaptor. Make sure spring is fitted as shown – short end at the top.
 - **Warranty voided if not fitted correctly.**
-  Fit rubber washer inside Handle and screw onto 3/4" unf male end of hose. No need for tape.
-  Fit rubber washer inside other end of Handle and screw on the Spray Valve.

❖ **Fitting to T&S / ENCORE / LWG.**

-  Remove 7/8 unf fine Hose Adaptor from top of the Spring Retainer.
-  Screw the (1/4" x 3/4") '**Adaptor 1**' provided in this pack onto 1/4" end of hose and then screw onto the 3/4" male thread on the Spring Retainer.
-  Slide Hook then Spring over hose and rest on Spring retainer. Make sure spring is fitted as shown – short end at the top.
 - **Warranty voided if not fitted correctly.**
-  Fit rubber washer inside Handle and screw onto 3/4" unf male end of hose. No need for tape.
-  Fit rubber washer inside other end of Handle and screw on the Spray Valve – either ours or existing.

❖ **Fitting to Enware / Galvin.**

-  **Option 1** - Screw the '**Adaptor 2**' (1/4" x 1/2') & '**Adaptor 3**' (3/4" x 1/2') provided in this pack onto ends of hose and then screw one end onto the 1/2" male thread on the Spring Retainer. **Option 2** - Screw the (1/4" x 1/2) '**Adaptor 2**' onto hose only.
-  Slide Hook then Spring over hose and rest on Spring Retainer. Make sure spring is fitted as shown – (short end at the top).
 - **Warranty voided if not fitted correctly.**
- **Option 1** - Screw the existing Spray valve onto end of hose.
- **Option 2** - Leave Adaptor 3 off the hose and fit as below.
-  Fit rubber washer inside Handle and screw onto 3/4" unf male end of hose. No need for tape.
-  Fit rubber washer inside other end of Handle and screw on the Spray Valve – either ours or existing Enware valve .

****We recommend the use of PST liquid sealant on all threaded joints where applicable. Not required on our handle**