

**PRODUCT NAME:**


'GLOBAL STAINLESS' Series  
S/S EXPOSED FIXED BREACH HOB TAP  
WITH S/S STANDARD SWIVEL SPOUT

**PART NUMBER:**

GS04S3006 + OTHERS (see chart below)

**DESCRIPTION:**

S/S EXPOSED FIXED BREACH HOB TAP BODY  
c/w S/S STANDARD SWIVEL SPOUT  
WITH 360 DEGREE SWIVEL CHECK STEMS  
JUMPER VALVES.

**TECHNICAL INFORMATION:**

- IDEAL WORKING PRESSURE = 65 - 100 PSI
- MAXIMUM PRESSURE = 200 PSI STATIC (in short periods)
- MIN. EFFECTIVE PRESSURE = 50 PSI
- WORKING TEMPERATURE 5 C - 65 C
- SHIPPING WEIGHT - 1.3 KG

**SUPPLIED WITH:**

- S/S EXPOSED FIXED BREACH HOB MOUNT TAP w/- S/S SPOUT
- S/S 1/2" ALL-THREAD w/- MOUNTING FLANGE & NUT
- S/S 360 DEGREE SWIVEL SPRING CHECK STEMS JUMPER VALVES

**FEATURES:****TAP BODY:**

- S/S (304) EXPOSED FIXED HOB TAP BODY
- S/S INTERNAL WORKINGS
- 360 DEGREE SWIVEL CHECK STEMS JUMPER VALVES.
- CP. LEVER HANDLES (SMALL FLAT EDGED SHAPE)
- 90 degree MOUNTING ADAPTORS

**WELS**

TAP w/- SPOUT - 3 STAR, 9lpm

REF	MODEL	LENGTH	Pt. No. TAP & SPOUT
A	6" MODEL	179mm	<b>GS04S3006</b>
B	8" MODEL	227mm	<b>GS04S3008</b>
C	10" MODEL	276mm	<b>GS04S3010</b>
D	12" MODEL	326mm	<b>GS04S3012</b>
E	14" MODEL	376mm	<b>GS04S3014</b>

**WATERMARK & WELS:**

Global Tapware Pty Ltd is a Watermarked, level 1, Company.  
All relevant products & components are WELS registered.

**Special Notice:**

- 1 - We reserve the right to make changes to products and drawings without notice.
- 2 - All drawings & Documents are subject to copyright ©.
- 3 - Seek written consent by us to reprint / use for other than specification work.

**'GLOBAL STAINLESS' Series****PT. NO.- GS04S3006 + OTHER**

S/S EXPOSED FIXED BREACH HOB TAP with Std SWIVEL SPOUT

