GLOBAL TAPWARE

'Global Accessories'

QUIK RELEASE COUPLINGS & PLUGS

In Chrome Brass & 304 S/S

½" CP Brass COUPLINGS



½" Female COUPLING CP
Pt No.:- **GQR12COUP-F-CP**
RRP $_____ + GST



½" Male COUPLING CP
w- AUTO SHUT OFF
Pt No.:- **GQR12COUP-AS-M-CP**
RRP $_____ + GST



AS COUPLING & PLUG
Pt. No. **GQR12COUP-AS-PLUG-CP**

½" CP Brass PLUGS

½" Male PLUG CP
Pt No.:- **GQR12PLUG-M-CP**
RRP $_____ + GST




½" Female PLUG CP
Pt No.:- **GQR12PLUG-F-CP**
RRP $_____ + GST



½" S/S Coupling & PLUG

½" Female COUPLING CP
Pt No.:- **GQR12COUP-F-SS**
RRP $_____ + GST



½" Male PLUG SS
Pt No.:- **GQR12PLUG-M-SS**
RRP $_____ + GST



3/4" CP Coupling & PLUG



3/4" Female COUPLING CP
with **AUTO SHUT OFF**
Pt No.:- **GQR34COUP-AS-F-CP**
RRP $_____ + GST



3/4" Male PLUG CP
Pt No.:- **GQR34PLUG-M-CP**
RRP $_____ + GST

Features:

- Suit Hot & Cold.
- Available with Auto Shut Off Coupling (Safety Feature)
- Chrome Brass Couplings c/w 3 ball bearing capture.
- S/S Couplings c/w 6 ball Bearing capture.
- Sizes available ½" & ¾"

WARRANTY:

- 12 Months for Commercial use and on material only.
- Bad install or incorrect use is not warranted.
- Exceeding pressure & temperature not warranted.
- Choosing 3 Ball bearing where 6 ball bearing should have been used is not warranted.

3 Ball Bearings



6 Ball Bearings



Technical:-

Chrome Plated Brass Fitting:

Seals / O'Rings	: **Nitrile (NBR)**
Working Press.	: **500kpa.** (NPC)
Max. Press. rate	: **2,500kpa.**
Operating Temp.	: **-30 - 80^0 C.**

Stainless Steel Fitting:

Seals / O'Rings	: **Viton**
Working Press.	: **500kpa.** (NPC)
Max. Press. rate	: **2,500kpa.**
Operating Temp.	: **-20 - 150^0 C.**

Global Tapware Pty Ltd
E – info.tech@globaltapware.com
P – 07 38 55 2350
P – 1300 85 25 15
W- **GLOBALTAPWARE.COM.AU**