GLOBAL WASHWARE
– HOT WASH HOSES -

Rubber Multi-Purpose Hose

- Suitable for Hot Water In washdown applications.
- Resistant to Crushing & Abrasion.
- Non-conductive at 1000 volts D.C.
- Special Nitrile Rubber resistant to oils & some chemicals.



REEL INLET HOSE

-Fitted w- ½" Male x3/4" Female

01mt Pt. No. **GTHW01-IH**



HOT WASH RED RUBBER HOSES

-Fitted w- ½" Male x ½" Female

01mt Pt. No. **GTHWHMF01**
02mt Pt. No. **GTHWHMF01**
05mt Pt. No. **GTHWHMF01**
10mt Pt. No. **GTHWHMF01**
15mt Pt. No. **GTHWHMF01**
20mt Pt. No. **GTHWHMF01**
30mt Pt. No. **GTHWHMF01**
40mt Pt. No. **GTHWHMF01**

TECHNICAL:

TEMPERATURE:	-20^0 C to + 95^0 C
TUBE:	Black, Smooth, Synthetic Rubber.
REINFORCEMENT:	High Strength Synthetic Yarn.
COVER:	Red, Smooth, Synthetic Rubber, Weathering & Ozone Resistant

GLOBAL TAPWARE Pty Ltd
P – 1300 85 25 15
E – info.tech@globaltapware.com
W – globaltapware.com.au